

Kwik Lite.

Features

- SAVES ENERGY UPTO 60%
- CONSTANT LUMEN 120 – 265V
- PRODUCES LESS HEAT
- LIGHT WEIGHT
- HIGHLY RELIABLE
- NO MERCURY



Model: KLTL - 020

Technical Specifications

Model	KLTL - 020
Power Supply	In-Built
Lamp	T8 LED Tube
LED Make	Seoul, Edison, Cree, Everlight, Galaxy or Equivalent
Operating Voltage Range	120 - 265 Volts AC/DC
Nominal Operating Voltage	230V AC $\pm 10\%$
Rated Input Current	0.09Amps (90mA) $\pm 10\%$
Rated Input Power	20 $\pm 10\%$ W
Power Factor	0.95 ± 0.05
Illumination	Constant from 120-265V AC/DC
No of LED's	120 LEDs
Colour Temperature	>6000° K
Lumen factor	≥ 0.95
Safety Features:	a) Output Short Circuit protected
	b) In-Built fuse provided
	c) Can withstand 300V AC for 60 minutes and 400V AC for 2 minutes.
Casing	Aluminium Extrusion Provided
Temperature rise	20°C above ambient (Max.)
Noise Level	Nil
Dimensions	Retrofit for T8, 4' feet FTL.

Contact us at: Premier Combines, Plot No.4 Mohammad Hussain Colony, Kolathur, Chennai – 600099.
Ph/Fax No.: 044-26510195, Visit us at: www.kwiklite.com Email: kwiklite@vsnl.com.